

ALPHA ASSOCIATES, INC.

145 LEHIGH AVE CN2013 LAKEWOOD, N.J. 08701
Phone: (732) 634-5700 Fax: (732) 634-1430

ALPHA
STYLE 3478-VS-2



DESCRIPTION

Style 3478-VS-2 is a lightweight vinyl coated fiberglass. Style 3478 -VS-2 meets the requirements of UL 181, Class 1.

APPLICATIONS

This product is designed for use as a core material for flexible duct applications and can also be used as a facing material for sound attenuating blankets and many other applications.

PROPERTY DATA

STYLE 3478-VS-2

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-3776-96	5.4 oz/sy \pm 10%	183 g/m ² \pm 10%
THICKNESS	ASTM-D-1777-96	0.005" \pm 0.001"	0.127 mm \pm .025 mm
TENSILE STRENGTH	ASTM-D-5035-95	Warp- 75 lbs/in. Fill- 70 lbs/inch	13.40 kg/cm 12.50 kg/cm
TEAR STRENGTH	ASTM-D-1424-96	Warp- 42.33 oz. Fill- 31.75 oz.	1200 gms. 900 gms.
MULLEN BURST	ASTM-D-3786-87	200 psi	14 kg/cm ²
FLAMMABILITY	FED 191/5903.2	Char Length 2 inches max Afterglow 2 seconds max. Flameout 2 seconds max.	5.08 cm max. 2 seconds max. 2 seconds max.
ABRASION RESISTANCE	ASTM-D-3389-94	Wheels - H22 Load - 500 g. Revolutions - 200 End point - Break in Yarns	
COLOR		Silver	
APPEARANCE		No pin holes	

DATA SHEET 13055

REV C

DATE: 4/25/07

* All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.