

ALPHA ASSOCIATES, INC.

145 LEHIGH AVENUE LAKEWOOD, N.J. 08701
Phone: (732) 634-5700 Fax: (732) 634-1430

ALPHA - WELD
STYLE 6445-2-SN



DESCRIPTION

Alpha-Weld Style 6445-2-SN is an economy grade Neoprene coated fiberglass welding curtain material. The incombustible fiberglass fabric is coated with a fire retardant salmon colored Neoprene.

APPLICATIONS

Alpha-Weld Style 6445-2-SN can be used for vertical welding curtains for spark and spray containment, grinding shields, arc flash barriers and fire retardant weather barrier material.

ADVANTAGES

The coating provides high visibility for safety and resistance to sparks, abrasion, water and most chemicals.

PROPERTY DATA *STYLE 6445-2-SN*

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-37766	13.5 oz/sy \pm 10%	459 g/m ² \pm 10%
THICKNESS	ASTM-D-1777	0.015" \pm .001"	0.381 mm \pm .025 mm
TENSILE STRENGTH	ASTM-D-5034	Warp- 300 lbs./inch Fill- 270 lbs./inch	53.58 kg/cm 48.22 kg/cm
TEAR STRENGTH	ASTM-D-5587	Warp- 35 lbs. Fill- 30 lbs.	15.88 kg 13.61 kg
BURST STRENGTH	ASTM-D-3786	475 psi	33.25 kg/cm ²
FLAME RESISTANCE	FED 191/5903.2	Char Length 1 inch max. Afterglow 1 sec. max. Flame Out 0 sec.	2.54 cm max. 1 sec. max. 0 sec.
TEMPERATURE RESISTANCE	FED SPEC HHB 100B	0 °F to +300 °F	-18 °C to 149 °C
BASE FABRIC and WEAVE		Fiberglass (100%) / Plain Weave	
COLOR and COATING		Salmon Neoprene	

DATA SHEET 13113

REV C

DATE: 9/26/08

* All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.