

ALPHA ASSOCIATES, INC.

145 LEHIGH AVE CN2013 LAKEWOOD, N.J. 08701
Phone: (732) 634-5700 Fax: (732) 634-1430

ALPHA - MARITEX
STYLE 8451-SR



DESCRIPTION

Alpha Maritex Style 8451-SR is a heavy duty fiberglass fabric coated with a special fire-retardant silicone rubber compound. The compound is red/orange in color, making it highly visible.

APPLICATIONS

This product is designed to be used as a welding curtain in a vertical or near vertical orientation.

ADVANTAGES

Alpha Style 8451-SR provides a high visibility , abrasion resistant, fire-retardant barrier to welding sparks and flash.

PROPERTY DATA *STYLE 8451-SR*

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<i>ENGLISH</i>	<i>METRIC</i>
WEIGHT	ASTM-D-3776-96	32.5 oz/sy \pm 10%	1105 g/m ² \pm 10%
THICKNESS	ASTM-D-1777-96	0.037" \pm 0.001"	0.940 mm \pm .025 mm
TENSILE STRENGTH	ASTM-D-5034-95	Warp- 350 lbs/inch Fill- 200 lbs/inch	62.51 kg/cm 35.72 kg/cm
TEAR STRENGTH	ASTM-D-5587-96	Warp- 50 lbs. Fill- 50 lbs.	22.68 kg 22.68 kg
MULLEN BURST	ASTM-D-3786-87	1000 psi	70 kg/cm ²
FLAME RESISTANCE	FED 191/5903.2	Char Length 1 inch max. Afterglow 1 sec. max. Flameout 5 sec. max.	2.54 cm max. 1 sec. max. 5 sec. max.
TEMPERATURE RESISTANCE	FED SPEC HHB-100B	-110 °F to 500 °F	-79 °C to 260 °C
BASE FABRIC and WEAVE		Fiberglass/Stain Weave	
COLOR and COATING		Red/Orange Silicone Rubber	

DATA SHEET 13111

REV B

DATE: 10/1/98

* All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.