

# ALPHA ASSOCIATES, INC.

145 LEHIGH AVENUE LAKEWOOD, N.J. 08701  
Phone: (732) 634-5700 Fax: (732) 634-1430

ALPHA  
STYLE 9678-VS-2



## DESCRIPTION

Alpha Style 9678-VS-2 is a medium vinyl coated fiberglass. This product meets the requirements of UL 181, Class 1.

## APPLICATIONS

Style 9678-VS-2 is designed for use as a core material for flexible duct applications and can also be used as a facing material for sound attenuating blankets and many other applications.

---

## *PROPERTY DATA*

### *STYLE 9678-VS-2*

---

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-3776	6.5 oz/sy $\pm$ 10%	221 g/m <sup>2</sup> $\pm$ 10%
THICKNESS	ASTM-D-1777	0.006" $\pm$ .10%	0.152 mm $\pm$ 10%
TENSILE STRENGTH	ASTM-D-5035	Warp- 125 lbs/inch Fill- 120 lbs/inch	22.33 kg/cm 21.43 kg/cm
TEAR STRENGTH	ASTM-D-1424	Warp- 88.18 oz. Fill- 105.82 oz.	2500 gms. 3000 gms.
MULLEN BURST	ASTM-D-3786	275 psi	19.25 kg/cm <sup>2</sup>
FLAME RESISTANCE	FED 191/5903.2	Char Length 1 inch max.	2.54 cm max.
		Afterglow 1 sec. max.	1 sec. max.
		Flame Out 0 sec. max.	0 sec. max.
ABRASION RESISTANCE	ASTM-D-3389	Wheel-H22 Load-500g Revolutions-250 End Point - Break in Yarns	
COLOR		Silver	
APPEARANCE		No Pinholes	

DATA SHEET 12843

REV B

DATE: 10/1/98

\* All values are nominal unless otherwise specified.

### **Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications**

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.