

MSDS *Material Safety Data Sheet*

Alpha Associates, Inc.



Alpha Style 4313 HSU-DS

MSDS Number: 0295

Revision Date: 6/22/2010

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Alpha Associates, Inc.
145 Lehigh Avenue

Lakewood, NJ 08701

Contact: James Palmer
Telephone Number: 732-634-5700
FAX Number: 732-634-1430
E-Mail: jpalmer@alphainc.com
Web: www.alphainc.com

Product Name: Alpha Style 4313 HSU-DS
Revision Date: 6/22/2010
MSDS Number: 0295
Common Name: Coated Film/ Scrim

2 COMPOSITION/INFORMATION ON INGREDIENTS

Fibrous Glass (CAS 14808-60-7)
ACGIH TLV: 10 milligrams per cubic meter of air fiber diameters of less than 7 microns

Polyester Film

Urethane Coating

3 HAZARDS IDENTIFICATION

Route of Entry: This material may enter the body through inhalation of nuisance dust.
Target Organs: Respiratory system
Inhalation: Sore, raspy throat
Skin Contact: Redness and possible rash; itching
Eye Contact: Itching and redness
Ingestion: N/A

4 FIRST AID MEASURES

Inhalation: Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact: Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
Eye Contact: Rinse with water. Do not rub eyes. Seek medical attention.
Ingestion: Not applicable.

MSDS *Material Safety Data Sheet*

Alpha Associates, Inc.



Alpha Style 4313 HSU-DS

MSDS Number: 0295

Revision Date: 6/22/2010

Page 2 of 4

5 FIRE FIGHTING MEASURES

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

6 ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

7 HANDLING AND STORAGE

Handling Precautions: Use adequate material handling equipment.

Storage Requirements: Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Local exhaust; dust collection

Protective Equipment: Safety glasses; cotton gloves; long sleeve clothing

Exposure Guidelines/Other: Wash thoroughly with soap and water after handling

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Silver one side/white scrim fabric other

Physical State: Solid

Odor: No odor

pH: N/A

Vapor Pressure: N/A

Vapor Density: N/A

Boiling Point: N/A

Freezing/Melting Pt.: > 150 F

Solubility: Negligible

Spec Grav./Density: 1.6



10 STABILITY AND REACTIVITY

Stability: Material is stable.

Conditions to avoid: None known.

Materials to avoid (incompatibility): Strong oxidizing agents.

Hazardous Decomposition products: Carbon monoxide; carbon dioxide; nitrogen oxide; cyanide

Hazardous Polymerization: Will Not Occur.

11 TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

12 ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 micrometers.

13 DISPOSAL CONSIDERATIONS

Burial in a federal, state, or local approved landfill.

14 TRANSPORT INFORMATION

None special required.

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Silica, crystalline (14808607 n/a%) MASS, NRC, OSHAWAC, PA, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

MSDS *Material Safety Data Sheet*

Alpha Associates, Inc.



Alpha Style 4313 HSU-DS

MSDS Number: 0295

Revision Date: 6/22/2010

Page 4 of 4

END OF MSDS DOCUMENT