

MSDS *Material Safety Data Sheet*

Alpha Associates, Inc.



Alpha Style VR-R Plus

MSDS Number: 0901

Revision Date: 6/21/10

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Alpha Associates, Inc.
145 Lehigh Avenue

Lakewood, NJ 08701

Contact: James Palmer
Telephone Number: 732-634-5700
FAX Number: 732-634-1430
E-Mail: jpalmer@alphainc.com
Web www.alphainc.com

Product Name: Alpha Style VR-R Plus
Revision Date: 6/21/10
MSDS Number: 0901
Common Name: Film/ Scrim/ Film Laminate

2 COMPOSITION/INFORMATION ON INGREDIENTS

Fibrous Glass (CAS 14808-60-7)
ACGIH TLV: 10 milligrams per cubic meter of air fiber diameters of less than 7 microns

Antimony oxide (Sb₂O₃) (CAS 1309-64-4)

Decabromodiphenyl oxide (CAS 1163-19-5)

Polypropylene Film

Polyester Film

Acrylic Adhesive

3 HAZARDS IDENTIFICATION

Route of Entry: This material may enter the body through inhalation of nuisance dust.

Target Organs: Respiratory system

Inhalation: Sore, raspy throat

Skin Contact: Redness and possible rash; itching

Eye Contact: Itching and redness

Ingestion: N/A



4 FIRST AID MEASURES

- Inhalation:** Remove person to fresh air. If condition persists, seek medical attention.
- Skin Contact:** Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
- Eye Contact:** Rinse with water. Do not rub eyes. Seek medical attention.
- Ingestion:** Not applicable.

5 FIRE FIGHTING MEASURES

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

6 ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

7 HANDLING AND STORAGE

- Handling Precautions:** Use adequate material handling equipment.
- Storage Requirements:** Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering Controls:** Local exhaust; dust collection
- Protective Equipment:** Safety glasses; cotton gloves; long sleeve clothing
- Exposure Guidelines/Other:** Wash thoroughly with soap and water after handling

MSDS Material Safety Data Sheet

Alpha Associates, Inc.



Alpha Style VR-R Plus

MSDS Number: 0901

Revision Date: 6/21/10

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White laminate	Boiling Point:	N/A
Physical State:	Solid	Freezing/Melting Pt.:	> 250 F
Odor:	No odor	Solubility:	Negligible
pH:	N/A	Spec Grav./Density:	1.8
Vapor Pressure:	N/A		
Vapor Density:	N/A		

10 STABILITY AND REACTIVITY

Stability:	Material is stable.
Conditions to avoid:	None known.
Materials to avoid (incompatibility):	Strong oxidizing agents.
Hazardous Decomposition products:	Carbon monoxide; carbon dioxide; hydrogen bromide
Hazardous Polymerization:	Will Not Occur.

11 TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

12 ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13 DISPOSAL CONSIDERATIONS

Burial in a federal, state, or local approved landfill.

14 TRANSPORT INFORMATION

None special required.

MSDS Material Safety Data Sheet

Alpha Associates, Inc.



Alpha Style VR-R Plus

MSDS Number: 0901

Revision Date: 6/21/10

Page 4 of 4

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Silica, crystalline (14808607 n/a%) MASS, NRC, OSHAWAC, PA, TXAIR

*Antimony oxide (Sb2O3) (1309644 n/a%) CERCLA, CSWHS, EPCRAWPC, MASS, PA, PROP65, TXAIR

*Decabromodiphenyl oxide (1163195 n/a%) MASS, NJHS, PA, SARA313

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous substances
EPCRAWPC = EPCRA Water Priority Chemicals
PROP65 = CA Prop 65

NJHS = NJ Right-to-Know Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals

16

OTHER INFORMATION

END OF MSDS DOCUMENT