



ALPHA - ALAFLEX (SCRIM BASE)
STYLE 59-M WHITE / PS

DESCRIPTION

Alpha Style 59-M White / PS is the matching pressure sensitive tape for Alpha Style 59M White. Alpha Style 59-M White is a lamination of 100% fiberglass scrim and polyester film. It is laminated using a white, high temperature-resistant, fire-retardant adhesive.

ADVANTAGES

- Resistant to oil and water
- Tough - resists damage and has excellent puncture resistance
- High tear strength
- White color eliminates need for painting
- Surface is paintable, if desired

APPLICATIONS

Matching seaming tape for 59M White

PROPERTY DATA

STYLE 59-M WHITE / PS

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-3776	4.8 oz/sy ± 10%	163 g/m ² ± 10%
THICKNESS	ASTM-D-1777	.010" nominal	0.254 mm nominal
TENSILE STRENGTH	ASTM-D-5035	Warp- 50 lbs/inch	8.93 kg/cm
		Fill- 50 lbs/inch	8.93 kg/cm
TEAR STRENGTH	ASTM-D-5587	Warp- 7 lbs	3.18 kg
		Fill- 7 lbs	3.18 kg
BEACH PUNCTURE	ASTM-C-1136	400 units (106 inch-lbs)	12.0 joules
ADHESION	ASTM-D-3330	Laminate Tear	Laminate Tear
PERMEABILITY (MVTR)	ASTM-E-96	Result - 0.5 Perms	
CORROSION RESISTANCE	ASTM C-1258	120 °F 95% RH 20 days	49 °C
		Result - No Corrosion	

Complies to US Coast Guard CFR 164.112, US Coast Guard Certificate of Approval Number 164.112/135/0

DATA SHEET: 13790 REV: H DATE: 4/17/2017 *All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.