



ALPHA

engineered composites

145 Lehigh Avenue, Lakewood, NJ 08701

T: 732.634.5700 F: 732.634.1430 alphainc.com

ALPHA - TEMP (FABRIC BASE)

STYLE 7642/9480 BH PS

DESCRIPTION

Alpha Style 7642/9480-BH-PS is a lamination of fiberglass fabric and aluminum foil with a pressure sensitive backing for use in automotive heat shields.

PROPERTY DATA

STYLE 7642/9480 BH PS

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-3776	11.7 oz/sy ± 10%	397.11 g/m ² ± 10%
THICKNESS	ASTM-D-1777	0.016" ± .001"	0.406 mm ± 0.025 mm
TENSILE STRENGTH	ASTM-D-5035	Warp- 250 lbs./inch Fill- 120 lbs/inch	44.69 kg/cm 21.45 kg/cm
TEAR STRENGTH	ASTM-D-5587	Warp- 20.0 lbs Fill- 20.0 lbs.	9.08 kg 9.08 kg
MULLEN BURST	ASTM-D-3786	200 psi	13.97 kg/cm ²
FLAME RESISTANCE			
BASE FABRIC and WEAVE		Fiberglass/Plain Weave	
COLOR and COATING		Aluminum Foil	
PEEL ADHESION	ASTM-D-3330	2 lbs./inch	357 g/cm

DATA SHEET: 14018 REV: C DATE: 11/2/2015 *All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.