



ALPHA - ALAFLEX  
STYLE 8101-2-SS

DESCRIPTION

Alpha Alaflex Style 8101-2-SS silver grey is a fiberglass fabric coated with a flame retardant, silicone elastomer.

APPLICATIONS

This product is designed specifically for flexible duct applications where high temperature resistance is a necessity.

ADVANTAGES

The special high temperature elastomer provides greater life and improved resistance to abrasion, flexing, tearing and puncture.

PROPERTY DATA  
STYLE 8101-2-SS

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-3776	12.0 oz/sy ± 10%	408 g/m <sup>2</sup> ± 10%
THICKNESS	ASTM-D-1777	0.014" ± .001"	0.356 mm ± .025 mm
TENSILE STRENGTH	ASTM-D-5034	Warp- 250 lbs./inch Fill- 250 lbs/inch	44.65 kg/cm 44.65 kg/cm
TEAR STRENGTH	ASTM-D-5587	Warp- 50 lbs Fill- 50 lbs	22.68 kg 22.68 kg
BURST STRENGTH	ASTM-D-3786	550 psi	38.5 kg/cm <sup>2</sup>
FLAME RESISTANCE	ASTM-D-6413	Char Length 0.5 inch max. Afterglow 1 sec. max. Flame Out 1 sec. max.	1.27 cm max. 1 sec. max. 1 sec. max.
TEMPERATURE RESISTANCE		-65 °F to +500 °F Continuous Service	-54 °C to 260 °C
CORROSION RESISTANCE	ASTM-C-1136	120 °F @95% RH 20 days Result - Passes	49 °C

DATA SHEET: 13083 REV: B DATE: 10/1/98 \*All values are nominal unless otherwise specified.

**Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications**

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.