



ALPHA

high performance fabrics & composites

ALPHA ASSOCIATES, INC. • 145 LEHIGH AVE. • LAKEWOOD, NJ 08701
 T: 732.634.5700 • 800.631.5399 • F: 732.634.1430

ALPHA - MARITEX
 STYLE 84215/9480-BH-PS

DESCRIPTION

Alpha Style 84215/9480-BH-PS is a lamination of fiberglass fabric and aluminum foil with a pressure sensitive backing for use in automotive heat shields.

PROPERTY DATA
 STYLE 84215/9480-BH-PS

<u>CHARACTERISTIC</u>	<u>METHOD</u>	<u>VALUES*</u>	
		<u>ENGLISH</u>	<u>METRIC</u>
WEIGHT	ASTM-D-3776	12.2 - 14.76 oz./sq. yd.	457 g/m ² ± 9.5%
THICKNESS	ASTM-D-1777	0.017 - 0.023 in.	0.508 mm ± .076 mm
TENSILE STRENGTH	ASTM-D-5035	Warp- 200 lbs./in. Min. Fill- 125 lbs./in. Min.	35.75 kg/cm 22.34 kg/cm
TEAR STRENGTH	ASTM-D-5587	Warp- 25 lbs. Min. Fill- 25 lbs. Min.	11.35 kg 11.35 kg
MULLEN BURST	ASTM-D-3786	200 psi Min.	13.97 kg/cm ²
PEEL Adhesion	ASTM-D-3330	2.0 lbs/inch	357 g/cm
COLOR and COATING		Aluminum Foil	
BASE FABRIC and WEAVE		Fiberglass/Plain Weave	
TEMPERATURE RESISTANCE		425 °F max.	218 °C max.

DATA SHEET: 14026 REV: F DATE: 10/4/16 *All values are nominal unless otherwise specified.

Specializing in marine, aerospace, automotive and commercial fabrics for thermal and industrial applications

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.