



ALPHA ASSOCIATES, INC. • 145 LEHIGH AVENUE • LAKEWOOD, NJ 08701
T: 732.634.5700 • 800.631.5399 • F: 732.634.1430

Product Bulletin

Item Code: EXP 15WF
(*comparable to FD-0005)

Description:

Alpha's code EXP-15WF is a fluorosilicone coated polyester that has a nominal temperature range of -65°F to 300°F. The Fluorosilicone used in the manufacturing process is a premium polymer providing excellent chemical and fuel resistance. Using polyester as the re-enforcement substrate provides good stability for the fluorosilicone in dynamic applications. The EXP-15WF offers excellent chemical resistance in many different fuel mixtures over a broad temperature range.

<u>Coated Fabric Property</u>	<u>Test Method</u>	<u>Typical Results</u>
Coating		Fluorosilicone
Color	Visual	Red
Width	ASTM D751	45" usable
Gauge	ASTM D751	.015 +/- .015
Grab Tensile (W x F)	ASTM D751	100 x 100 min
Mullen Burst	ASTM D751	150 psi min

Alpha Associates warrants the aforementioned product is free from defects in material and workmanship when used as recommended. Alpha Associates will only replace the product that is shown to our satisfaction to be defective within 30 days of delivery without charge. Defects or damage resulting from use other than recommended or misuse of any kind are not covered by this Limited Liability. These recommendations are not to be construed as warranties of any kind. Since conditions of use are beyond the control of Alpha Associates, the user assumes all risks of use. Alpha Associates will not be responsible for claims beyond the purchase value of the product. No sales representative, agent or distributor is authorized to extend any guarantee or warranty beyond the above terms. All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guarantee or warranty.

*FD-0005 is an item code used by others in the rubber industry