

Alpha Style 59-M White PS Tape

1 **PRODUCT AND COMPANY IDENTIFICATION**

Product Identifier: Alpha Style 59-M White PS Tape
Common Name: Film/ Scrim Laminate
SDS Number: 0346
Revision Date: 9/16/2016
Supplier Details: Alpha Associates, Inc.
145 Lehigh Avenue
Lakewood, NJ 08701

Contact: James Palmer
Phone: 732-634-5700
Fax: 732-634-1430
Email: jpalmer@alphainc.com
Web: www.alphainc.com

2 **HAZARDS IDENTIFICATION**

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 3
Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:



GHS Hazard Statements:

H316 - Causes mild skin irritation
H335 - May cause respiratory irritation

GHS Precautionary Statements:

P264 - Wash _ thoroughly after handling.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: This material may enter the body through inhalation of nuisance dust.
Target Organs: Respiratory system
Inhalation: Sore, raspy throat
Skin Contact: Redness and possible rash; itching
Eye Contact: Itching and redness
Ingestion: N/A

3 COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
65997-17-3		Fibrous Glass
1309-64-4		Antimony oxide (Sb203)
0		Polyester Film
0		Urethane Adhesive
0		Acrylic Adhesive
0		Silicone Coated Paper

Fibrous Glass (CAS 65997-17-3)

Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc

4 FIRST AID MEASURES

Inhalation:	Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact:	Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
Eye Contact:	Rinse with water. Do not rub eyes. Seek medical attention.
Ingestion:	Not applicable.

5 FIRE FIGHTING MEASURES

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

6 ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

7 HANDLING AND STORAGE

Handling Precautions:	Use adequate material handling equipment.
Storage Requirements:	Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Local exhaust; dust collection
Personal Protective Equipment:	HMIS PP, B Safety Glasses, Gloves Safety glasses; cotton gloves; long sleeve clothing

Wash thoroughly with soap and water after handling

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White Colored Fabric Reinforced Film/Pressure Sensitive Adhesive Back		
Physical State:	Solid	Odor:	No Odor
Spec Grav./Density:	1.8	Solubility:	Negligible
Boiling Point:	N/A	Freezing/Melting Pt.:	> 400 F
Vapor Pressure:	N/A	Vapor Density:	N/A
pH:	N/A		

10

STABILITY AND REACTIVITY

Chemical Stability:	Material is stable.
Conditions to Avoid:	None known.
Materials to Avoid:	Strong oxidizing agents.
Hazardous Decomposition:	Carbon monoxide; carbon dioxide; nitrogen oxide; cyanide; hydrogen bromide
Hazardous Polymerization:	Will Not Occur.

11

TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

12

ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13

DISPOSAL CONSIDERATIONS

Incineration preferred in a federal, state, or local approved facility.

14

TRANSPORT INFORMATION

None special required.

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [n/a%] TSCA

Antimony oxide (sb203) (1309-64-4) [n/a%] CERCLA, CSWHS, EPCRAWPC, MASS, PA, PROP65, TSCA, TXAIR

Polyester Film (0) [n/a%]

urethane Adhesive (0) [n/a%]

Acrylic Adhesive (0) [n/a%]

silicone Coated Paper (0) [n/a%]




Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act
 CERCLA = Superfund clean up substance
 CSWHS = Clean Water Act Hazardous substances
 EPCRAWPC = EPCRA Water Priority Chemicals
 MASS = MA Massachusetts Hazardous Substances List
 PA = PA Right-To-Know List of Hazardous Substances
 PROP65 = CA Prop 65
 TXAIR = TX Air Contaminants with Health Effects Screening Level

NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 1, Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).