



www.alphainc.com

**Alpha Engineered Composites** 

### Alpha Style FH2820-6 Blue

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier: Common Name: SDS Number: Revision Date:	Alpha Style FH2820-6 Blue Silicone Coated Glass Fabric 0886 2/9/2018
Supplier Details:	Alpha Engineered Composites LLC. 145 Lehigh Avenue Lakewood, NJ 08701
Contact: Phone: Fax: Email:	James Palmer 732-634-5700 732-634-1430 jpalmer@alphainc.com

Email: Internet:

SDS Number: 0886

# **Classification of Substance**

2

## GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 3 Health, Specific target organ toxicity - Single exposure, 3 Health, Reproductive toxicity, 1

# **GHS Label Elements, Including Precautionary Statements**

## GHS Signal Word: DANGER

## **GHS Hazard Pictograms:**



### **GHS Hazard Statements:**

H316 - Causes mild skin irritation

- H335 May cause respiratory irritation
- H360 May damage fertility or the unborn child

#### **GHS Precautionary Statements:**

P202 - Do not handle until all safety precautions have been read and understood.

P264 - Wash \_ thoroughly after handling.

P281 - Use personal protective equipment as required.

## Hazards not Otherwise Classified (HNOC) or not Covered by GHS

3	COMPOSITION/INFORMATION ON INGREDIENTS	
Ingestion:	N/A	
Eye Contact:	Itching and redness	
Skin Contact:	Redness and possible rash; itching	
Inhalation:	Sore, raspy throat	
Target Organs:	Respiratory System	
Route of Entry:	This material may enter the body through inhalation of nuisance dust.	

Chemical Ingredients		
CAS# % Chemical Name		
65997-17-3		Fibrous Glass
0		Compounded silicone coating
133-14-2		Peroxide, bis(2,4-dichlorobenzoyl)

Fibrous Glass (CAS 65997-17-3) Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc

## FIRST AID MEASURES

Inhalation:	Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact:	Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
Eye Contact:	Rinse with water. Do not rub eyes. Seek medical attention.
Ingestion:	Not applicable.

4

6

Flash Point (Method Used): >250 C by TOC Fla

Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

# ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidently released, rewind material back onto roll.

7	HANDLING AND STORAGE
Handling Precautions: Storage Requirements:	Use adequate material handling equipment. Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.
8	EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Local exhaust; dust collection	
Personal Protective	HMIS PP, B   Safety Glasses, Gloves	
Equipment:	Safety glasses; cotton gloves; long sleeve clothing	
Wash thoroughly with soap and water after handling		

9	PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Unbalanced Blue Silicone		
Physical State:	Solid	Odor:	No Odor
Specific Gravity or Density:	2.4	Solubility:	Negligible
Boiling Point:	N/A	Freezing or Melting Point:	> 1000 F
Vapor Pressure:	N/A	Vapor Density:	N/A
Potentia Hydrogenii:	N/A		

## STABILITY AND REACTIVITY

Chemical Stability:	Material is stable.
Conditions to Avoldentification:	None known.
Materials to Avoldentification:	Strong oxidizing agents.
Hazardous Decomposition: Hazardous Polymerization:	Carbon monoxide; carbon dioxide Will Not Occur.

# **TOXICOLOGICAL INFORMATION**

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

10

11

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13 DISPOSAL CONSIDERATIONS

Incineration perferred in a federal, state, or local approved facility.

14

15

16

TRANSPORT INFORMATION

No special requirement

# **REGULATORY INFORMATION**

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [n/a%] TSCA

Compounded silicone coating (0) [n/a%]

Peroxide, bis(2,4-dichlorobenzoyl) (133-14-2) [n/a%] TSCA

Regulatory CODE Descriptions

-----


TSCA = Toxic Substances Control Act

OTHER INFORMATION

**NFPA:** Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = None

**HMIS III:** Health = 1, Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

12