



ALPHA ASSOCIATES, INC. • 145 LEHIGH AVENUE • LAKEWOOD, NJ 08701
T: 732.634.5700 • 800.631.5399 • F: 732.634.1430

Product Bulletin

Item Code: ED-1635
(*comparable to CRP-5240)

Description: EPDM (Ethylene Propylene Diene Monomer) coated “anti-wicking” nylon for flat cut diaphragm type applications. The combination of EPDM and anti-wicking nylon fabric produces a coated fabric with excellent oxidation and ozone resistance.

<u>Coated Fabric Property</u>	<u>Test Method</u>	<u>Typical Results</u>
Color	Visual	Black
Anti-wicking Finish	Alpha Method	150 psi min
Width	ASTM D751	56” usable
Gauge	ASTM D751	.035”+/- .005”
Tensile Strength (W x F)	ASTM D751	250 x 250 min
Mullen Burst	ASTM D751	450 psi min
Adhesion	ASTM D751	3 lbs min

Alpha Associates warrants the aforementioned product is free from defects in material and workmanship when used as recommended. Alpha Associates will only replace the product that is shown to our satisfaction to be defective within 30 days of delivery without charge. Defects or damage resulting from use other than recommended or misuse of any kind are not covered by this Limited Liability. These recommendations are not to be construed as warranties of any kind. Since conditions of use are beyond the control of Alpha Associates, the user assumes all risks of use. Alpha Associates will not be responsible for claims beyond the purchase value of the product. No sales representative, agent or distributor is authorized to extend any guarantee or warranty beyond the above terms. All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guarantee or warranty.

*CRP-5240 is an item code used by others in the rubber industry