

## Alpha Style EH6425-2 UNS

## PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Alpha Style EH6425-2 UNS
Common Name: Silicone Coated Fiberglass Fabric

**SDS Number:** 1646 **Revision Date:** 12/19/2016

Supplier Details: Alpha Associates, Inc.

145 Lehigh Avenue Lakewood, NJ 08701

 Contact:
 James Palmer

 Phone:
 732-634-5700

 Fax:
 732-634-1430

Email: jpalmer@alphainc.com
Web: www.alphainc.com

# 2 HAZARDS IDENTIFICATION

## Classification of the Substance or Mixture

### GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 2

Health, Specific target organ toxicity - Single exposure, 3

Health, Reproductive toxicity, 1

## **GHS Label Elements, Including Precautionary Statements**

**GHS Signal Word: DANGER** 

## **GHS Hazard Pictograms:**





#### **GHS Hazard Statements:**

H315 - Causes skin irritation

H335 - May cause respiratory irritation

H360 - May damage fertility or the unborn child

## **GHS Precautionary Statements:**

P202 - Do not handle until all safety precautions have been read and understood.

P264 - Wash \_ thoroughly after handling.

P281 - Use personal protective equipment as required.

# Hazards not Otherwise Classified (HNOC) or not Covered by GHS

**Route of Entry:** This material may enter the body through inhalation of nuisance dust.

Target Organs:Respiratory SystemInhalation:Sore, raspy throat

**Skin Contact:** Redness and possible rash; itching

Eye Contact: Itching and redness

Ingestion: N/A

## 3

### **COMPOSITION/INFORMATION OF INGREDIENTS**

#### Ingredients:

Cas# % Chemical Name

0 Compounded silicone coating

0 Polyethylene Liner

0 Polyethylene Liner 65997-17-3 Fibrous Glass

133-14-2 Peroxide, bis(2,4-dichlorobenzoyl)

Fibrous Glass (CAS 65997-17-3)

Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable) ACGIH TLV 1 f/cc

#### 4

## **FIRST AID MEASURES**

**Inhalation:** Remove person to fresh air. If condition persists, seek medical attention.

**Skin Contact:** Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.

**Eye Contact:** Rinse with water. Do not rub eyes. Seek medical attention.

Ingestion: Not applicable.

## 5

## **FIRE FIGHTING MEASURES**

Flash Point (Method Used): >250 C by TOC Flammable Limits

LEL: N/A UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and

fumes.

Unusual Fire and Explosion Hazards: None

### 6

# **ACCIDENTAL RELEASE MEASURES**

Material is a solid in roll form. If accidently released, rewind material back onto roll.

#### 7

## **HANDLING AND STORAGE**

Handling Precautions: Use adequate material handling equipment.

**Storage Requirements:** Store in dry place. Use may be at temperature extremes based on product data, but storage should be

at ambient temperature.

#### 8

### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Controls: Local exhaust; dust collection

Personal Protective HMIS PP, B | Safety Glasses, Gloves

**Equipment:** Safety glasses; cotton gloves; long sleeve clothing

Wash thoroughly with soap and water after handling

### 9 PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Red Silicone On Both Sides of Fiberglass fabric

**Physical State:** Solid Odor: No Odor Spec Grav./Density: 2.4 Solubility: Negligible N/A Freezing/Melting Pt.: > 1000 F **Boiling Point: Vapor Pressure:** N/A Vapor Density: N/A

pH: N/A

## 10 STABILITY AND REACTIVITY

**Chemical Stability:** Material is stable. **Conditions to Avoid:** None known.

Materials to Avoid: Strong oxidizing agents.

Hazardous Decomposition: Carbon monoxide; carbon dioxide

Hazardous Polymerization: Will Not Occur.

# 11 TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

## 12 ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

## 13 DISPOSAL CONSIDERATIONS

Incineration perferred in a federal, state, or local approved facility.

### 14 TRANSPORT INFORMATION

No special needs

# 15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

-----

Compounded silicone coating (0) [n/a%]

Polyethylene Liner (0) [n/a%]

Fibrous Glass (65997-17-3) [n/a%] TSCA

Peroxide, bis(2,4-dichlorobenzoyl) (133-14-2) [n/a%] TSCA

Regulatory CODE Descriptions

-----

TSCA = Toxic Substances Control Act

## 16 OTHER INFORMATION


NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 1, Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves







### Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).